



The Turbo Cart 96A is designed to clean larger components where higher flow rates are required. Our standard model comes with all the features that others will add additional charges. The cart is also available with an electric pump.

## Key Features

- Finish Thompson Non-metallic Air Operated Double Diaphragm Pump with Santoprene Elastomers
- Dual gauges to monitor the entire cleaning process
- Gauge Guards to prevent gauge damage from chemicals
- In-line check valve to prevent any back flow flooding.
- True Union in-line ball valves
- Easily regulate flow rates from 1-125 gpm with 50' head
- 2 - 25' inlet/outlet hose, 10' suction, all hoses are reinforced chemical hoses
- 55-gallon on-board tank with drain and large 6" access for filling, venting, and cleaning
- Heavy duty 8" cast iron core wheels, with a polyurethane coating to allow smooth rolling and 4-wheel "full range" maneuverability when needed

## Applications

- Industrial Descaling Applications
- Heat Exchangers
- Boilers
- Plate and Frame Heat Exchangers
- Chillers/Absorbers
- Cooling Towers
- Medium size Condensers



**WHEELHOUSE**  
INDUSTRIES LLC  
Chemical Cleaning Maximized

800-567-1443  
[sales@wheelhouseindustries.com](mailto:sales@wheelhouseindustries.com)  
[wheelhouseindustries.com](http://wheelhouseindustries.com)



JULY2023